


# ECLISSE TELESCOPIC SINGLE

## SOLID WALL



SYSTEMS FOR 2 PARALLEL DOORS - Measures related to Italian standards, other dimensions available

PASSAGE SIZE <b>L x H</b>	OVERALL DIMENSIONS			DOOR PANEL*	
	<b>C x H1</b>	<b>A</b>	<b>B</b>	<b>DW</b>	<b>DH</b>
<b>1140 x 2000/2100</b>	1855 x 2090/2190	1190	625	615 ÷ 635	2010/2110
<b>1340 x 2000/2100</b>	2155 x 2090/2190	1390	725	715 ÷ 735	2010/2110
<b>1540 x 2000/2100</b>	2455 x 2090/2190	1590	825	815 ÷ 835	2010/2110
<b>1740 x 2000/2100</b>	2755 x 2090/2190	1790	925	915 ÷ 935	2010/2110
<b>1940 x 2000/2100</b>	3055 x 2090/2190	1990	1025	1015 ÷ 1035	2010/2110
<b>2140 x 2000/2100</b>	3355 x 2090/2190	2190	1125	1115 ÷ 1135	2010/2110
<b>2340 x 2000/2100</b>	3655 x 2090/2190	2390	1225	1215 ÷ 1235	2010/2110

FINISHED WALL= <b>FW</b>	BRICKS= <b>Br</b>	INTERNAL PASSAGE= <b>IP</b>	<b>X</b>
<b>150</b> →	120	114	48
<b>180</b> →	80+60	144	58

Dimensions are given in mm.

### NON STANDARD SIZES

- ▶ Passage width from 1140 to 2340 mm.
- ▶ Passage height from 1000 to 2600 mm.

### NOTES

- ▶ Max door weight 100 kg.
- ▶ Max door thickness 43 mm for FW=180 mm and 40 mm for FW=150 mm (including any glass holder for glazed door).
- ▶ When fully open, the door panels will protrude slightly from the jambs, so the passage width is reduced.
- ▶ ECLISSE counterframes can host any sliding door panel of standard dimensions available on the market.
- ▶ Install at finished floor level.
- \* Listed measures refers to wooden door panels only.

### ACCESSORIES

- ▶ Telescopic synchronisation
- ▶ ECLISSE BIAS®
- ▶ Anti-warp profile